

Ampoules



Ampoules LED	Article N°	Culot	Nombre LED	Eclairage	Tension	Intensité lumen	Dimensions mm	Consommation	Prix CHF		Types de culots	
	NIBAY15D15V	BAY15d	15	360°	10-30 V	200	55 x Ø 19	2.2 W	28.00	G		
	NIBA15D-10S	BA15d	10	360°	8-30 V	110	53 x Ø 19	1.1 W	22.00	G		
	NIBA15D-18S	BA15d	18	360°	8-30 V	220	54 x Ø 19	2.6 W	28.00	G		
	NIBA15S24V	BA15s	16	360°	24 V	32	53 x Ø 24.5	1.8 W	19.00	G		
	NIBA15S-15S	BA15s	15	360°	8-30 V	200	54 x Ø 19	2.2 W	27.00	G		
	NIBA15S-10S	BA15s	10	360°	8-30 V	120	54 x Ø 19	1.2 W	22.00	G		
	NISV366	SV8.5	3	120°	10-30 V	50	36 x Ø 13	0.6 W	11.00	G		
	NISV448	SV8.5	3	120°	10-30 V	506	41 x 13	0.6 W	13.00	G		
	NISV842-360	SV8.5	8	360°	12-15 V	110	42 x Ø 11	1.2 W	18.50	G		
	T0031	SV8.5	12	360°	6-32 V	120	44 x Ø 10	2.4 W	paire 26.00	C		
	NISC4415	SC	8	360°	12-15 V	110	42 x Ø 10	1.2 W	19.90	G		
	NIG4-12S	G4	12	180°	10-30 V	150	Ø 30.5	2 W	16.50	G		
	NIG4-6S	G4	6	180°	7-30 V	70	Ø 23	1.2 W	13.50	G		
	NISV316	SV8.5	6	120°	10-30 V	110	31 x 18	1.4 W	13.50	G		
	NIBA9S	BA9s	1	360°	12 V	110	32 x Ø 12	1.1 W	14.00	G		



Ampoules	Article N°	Culot	Watts	Volts	Dimensions mm	Recommandé pour	Prix CHF	
	AS400002	BAY15d	25 W	12 V	67 x Ø 25	séries AS 40 à 50	18.00	G
	AS400003	BAY15d	25 W	24 V	67 x Ø 25	séries AS 40 à 50	18.00	G
	AS400005	BAY15d	10 W	12 V	69 x Ø 25	séries AS 40 à 50	18.00	G
	AS400006	BAY15d	10 W	24 V	69 x Ø 25	séries AS 40 à 50	18.00	G
	AS400496	BA9s	5 W	12 V	26 x Ø 8	série AS 20	2.00	G
	AS400470	BA9s	20 W	12 V	28 x Ø 9	séries AS 25 + Sylt	12.00	G
	AS400755	BA15s	15 W	12 V	48 x Ø 25	AS133403	3.00	G
	AS400057	BA15d	10 W	12 V	30 x Ø 20		9.00	G
	AS400436	G4	5 W	12 V	29 x Ø 9		4.80	G
	AS400437	G4	10 W	12 V	29 x Ø 9		12.80	G
	AS379002270	navette (pointue)	10 W	12 V	30 x Ø 10	série AS 24	paire 8.50	G
	AS400200	navettes (1 plate + 1 pointue)	10 W	12 V	43 x Ø 10	série AS 25	5.50	G
	AS400201	navette (plate)	10 W	24 V	43 x Ø 10	série AS 25	4.00	G
	AS400177	navette (pointue) SV8.5-8	10 W	12 V	43 x Ø 10	série AS 25	2.00	G
	AS400190	navette (pointue) SV8.5-8	5 W	24 V	42 x Ø 10		3.00	G
	AS400191	navette (pointue) SV8.5-8	10 W	24 V	43 x Ø 11	série AS 25	4.00	G
	AS400307	PAR36 (halogène)	50 W	12 V	Ø 111	feu de pont	29.00	G
	AS400202	PAR36	50 W	24 V	Ø 111	projecteur à main	75.00	G
	AS400228	PAR36 (halogène)	50 W	12 V	Ø 111	projecteur à main	42.00	G