



SAFETY DATA SHEET

Treadmaster Marine Epoxy Adhesive Part A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Treadmaster Marine Epoxy Adhesive Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier TIFLEX LTD
TIFLEX HOUSE
TREBURGIE WATER
LISKEARD
CORNWALL
PL14 4NB
T: +44 (0) 1579 320 808
F: +44 (0) 1579 320 802
E: sward@tiflex.co.uk

1.4. Emergency telephone number

Emergency telephone +44 01579 320 808 (NOT 24HRS - 9am-5pm mon-thurs, 9am-4pm fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317


Environmental hazards Aquatic Chronic 2 - H411

Human health May cause sensitisation or allergic reactions in sensitive individuals.

Environmental The product contains a substance which is toxic to aquatic organisms.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Treadmaster Marine Epoxy Adhesive Part A

Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	REACTION PRODUCT; BISPHENOL -A- (EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT<=700), OXIRANE, MONO [(C12-14ALKYLOXY) METHYL] DERIVS, REACTION PRODUCT: BISPHENOL F- (EPICHLORHYDRIN): EPOXY RESIN
Supplementary precautionary statements	<p>P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P321 Specific treatment (see medical advice on this label). P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.</p>

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

REACTION PRODUCT; BISPHENOL -A(EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT<=700) CAS number: 25068-38-6 REACH registration number: 012119456619-26-0004	60-100%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
OXIRANE, MONO [(C12-14- ALKYLOXY) METHYL] DERIVS CAS number: 68609-97-2 REACH registration number: 012119485289-22-0000	10-30%
Classification Skin Irrit. 2 - H315 Skin Sens. 1 - H317	
REACTION PRODUCT: BISPHENOL F- (EPICHLORHYDRIN): EPOXY RESIN CAS number: 20864-14-4 EC number: 500-006-8	10-30%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
3-GLYCIDYLOXYPROPYL-TRIMETHOXYSILANE CAS number: 2530-83-8 REACH registration number: 012119513212-58-0010	1-5%

Treadmaster Marine Epoxy Adhesive Part A

Classification
Eye Dam. 1 - H318

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Irritation of nose, throat and airway. Coughing, chest tightness, feeling of chest pressure.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
----------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	The product is non-combustible. Irritating gases or vapours. Not known.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.
Special protective equipment	Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus for firefighters (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
----------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
---------------------------	--

Treadmaster Marine Epoxy Adhesive Part A

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours and spray/mists. Avoid contact with skin and eyes. Do not use in confined spaces without adequate ventilation and/or respirator. Spraying is permitted only in closed systems, spray cabinets or spray boxes with adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Wash hands after handling. When using do not eat, drink or smoke.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: Gas filter, type AX.

Thermal hazards

The molten product can cause serious burns.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

Treadmaster Marine Epoxy Adhesive Part A

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Various colours.
Odour	Characteristic.
Odour threshold	Not available.
pH	Not available.
Melting point	Not applicable.
Initial boiling point and range	Not applicable.
Flash point	>200°C CC (Closed cup).
Evaporation rate	slow
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not available.
Vapour density	Not applicable.
Relative density	1.63 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water. Hardens in contact with water.
Partition coefficient	Not available.
Auto-ignition temperature	>600°C
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	Not available.
Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Amines.
------------	---------

Treadmaster Marine Epoxy Adhesive Part A

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with water. Strong alkalis.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or products vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Moderately irritating.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Carcinogenicity

Carcinogenicity Not available.

Target organ for carcinogenicity No specific target organs known.

Reproductive toxicity

Reproductive toxicity development This substance has no evidence of toxicity to reproduction.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Inhalation Irritating to respiratory system.

Ingestion May cause stomach pain or vomiting.

Skin contact Irritating to skin.

Eye contact Irritation of eyes and mucous membranes.

Acute and chronic health hazards May cause respiratory system irritation. The product contains an epoxy resin.

Route of entry Inhalation Skin and/or eye contact

Medical symptoms Irritation of eyes and mucous membranes. Coughing, chest tightness, feeling of chest pressure.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment.

Treadmaster Marine Epoxy Adhesive Part A

12.1. Toxicity

Acute toxicity - fish	LC50, 96 hours: > 1000 mg/l, Freshwater fish
Acute toxicity – aquatic Invertebrates	EC ₅₀ , 48 hours: >500 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: ~ 1640 mg/l, Scenedesmus subspicatus

12.2. Persistence and degradability

Persistence and degradability	The product is not readily biodegradable.
Stability (hydrolysis)	Reacts with water.
Biological oxygen demand	< 10 g O ₂ /g substance

12.3. Bioaccumulative potential

Bioaccumulative potential	The product does not contain any substances expected to be bioaccumulating.
Partition coefficient	Not available.

12.4. Mobility in soil

Mobility	The product is non-volatile.
----------	------------------------------

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
------------------------------------	---

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction Product; Bisphenol A(Epichlorhydrin) Epoxy Resin (Average number molecular weight <=700))
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(Reaction Product; Bisphenol A(Epichlorhydrin) Epoxy Resin (Average number molecular weight <=700))
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction Product; Bisphenol A(Epichlorhydrin) Epoxy Resin (Average number molecular weight <=700))
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Reaction Product; Bisphenol A(Epichlorhydrin) Epoxy Resin (Average number molecular weight <=700))

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6

Treadmaster Marine Epoxy Adhesive Part A

ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). Control of Pollution Act 1974. Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Treadmaster Marine Epoxy Adhesive Part A

Issued by	Compliance
Revision date	23/05/2019
Revision	6
Supersedes date	20/06/2017
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Store Between	Store Between 5°C – 25°C

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.